

INFORMATION REPORT

COUNTRY Hungary

SUBJECT Nitrogen Works at Petfurdo

PLACE ACQUIRED [] 25X1A

DATE ACQUIRED BY SOURCE [] 25X1A

DATE OF INFORMATION []

DATE DISTR. 26 Apr 1954

NO. OF PAGES 2

NO. OF ENCLS.
(LISTED BELOW)

SUPPLEMENT TO
REPORT NO.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE
OF THE UNITED STATES, WITHIN THE MEANING OF TITLE 18, SECTIONS 793
AND 794, OF THE U.S. CODE, AS AMENDED. ITS TRANSMISSION OR REVE-
LATION OF ITS CONTENTS TO OR RECEIPT BY AN UNAUTHORIZED PERSON IS
PROHIBITED BY LAW. THE REPRODUCTION OF THIS FORM IS PROHIBITED.

THIS IS UNEVALUATED INFORMATION

SOURCE

25X1X

[]

1. [] 25X1X This factory, during
peace time, conducted various experiments for agricultural purposes and
during World War II was converted into making explosives.

2. [] 25X1X

3. "Data and Production Figures:

- a) The drinking water of the Power Plant is brought to the plant through separate pipe lines originating from two covered wells. The plant has a separate pipe line and pumping equipment for fire extinguishing. The Gas Plant can synthesize a maximum 40-50 tons of NH_3 per day. Average daily production amounts to 30-40 tons.
- b) The average production of the Ammonium Nitrate-Ammonium Salt Plant is 3 carloads of NH_4NO_3 per day. If another crystallizer were installed, 6 carloads of NH_4NO_3 could be produced daily. The manufacture of ammonium salts requires 3 carloads of NH_4NO_3 daily. The storeroom had a capacity of 2000 carloads of salt.
- c) Five carloads of Calcium Nitrate are produced daily.
- d) Pet produces 15 tons of chlorine per week. The chlorine is stored in four hundred kilogram tin boxes.
- e) The plant produces 1400 kilograms of Trichloroethylene daily.
- f) Production of Diamine amounts to 400 kilograms, 20% strength, in 24 hours.
- g) The Cracking Plant produces 13,000 tons of refined gasoline from motor gasoline annually. Annual production of fuel oil, gas oil, and distilled petroleum amounts to 6,200; 2,900; and

SEE LAST PAGE FOR SUBJECT & AREA CODES 25X1A
CLASSIFICATION CONFIDENTIAL

- 2 -

and 1,140 tons respectively. The fuel oil process nets 80 tons per day. These figures increased considerably by 1945.

4. "Daily Output of Pet Nitrogen Works:

Ammonia Synthesis 35-40 tons of NH_3
Dilute Nitric Acid 48-50% - 120-140M3
i.e. 75-87 tons of 100% HNO_3

Acid Concentration - 98% HNO_3 - 9-15 tons, or maximum 30 tons, 100% HNO_3

Ammonium Nitrate and Ammonium Salts average of 2 tons, or maximum 30 tons, explosive $\text{NH}_4 \text{NO}_3$ and a maximum of 112 tons of Ammonium Salts having a ratio $\text{NH}_4 \text{NO}_3 : \text{Ca CO}_3$

Calcium Nitrate Maximum of 50 tons of $\text{Ca} (\text{NO}_3)_2$

Carbon Disulphide Maximum of 6 tons of CS_2

Chlorine 2 tons of Cl_2 and 2 to 3 tons of solid Na OH

Sulphur Monochloride maximum of 3.3 tons of 57% $\text{S}_2 \text{Cl}_2$

Trichloroethylene maximum of 2 tons trichloroethylene, shop operates only when Sulphur Monochloride is not being produced.

Ethylendiamine 0.4 tons of ethylendiamine

Cracking Plant processes 60-90 tons of crude oil from which it prepares 60-65% gasoline; 18-20% fuel oil or petroleum coke; 8-10% gas oil.

Vaseline processes 10 tons of crude oil from which is prepared 1 ton of Vaseline."

-end-

LIBRARY SUBJECT & AREA CODES

4-5/711.271	37M
4-5/711.274	37M
4-5/711.272	37M
4-5/711.261	37M
4-5/735.611	37M
4-5/735.64	37M
4-5/735.63	37M
4-5/735.69	37M
4-5/711.223	37M
4-5/711.127	37M
4-5/711.126	37M

CONFIDENTIAL